

ENGLISH 



[WWW.SERWO.EU](http://WWW.SERWO.EU)

A black and white photograph of a rectangular LED light fixture with a ribbed heat sink, mounted on a workbench. The fixture is illuminated from within, creating a bright glow. In the foreground, there are various tools and materials, including a pencil, a ruler, and several white plastic fasteners. The image is framed by a large red diagonal shape that cuts across the top and bottom.

**Light  
Products!**

**#loveled**

# Luminaires for the professional user!

#loveled



5 YEARS GUARANTEE



## Magnum Battery XS Set



- Impact resistance: IK09
- Nominal power: 20 W
- Color temperature: 4000 K
- **Max. luminous flux: 2300 lm**
- Operating mode for battery-based operation for 2 Ah batteries:
  - 4 brightness levels:
    - 200 lm, working time: 15 h
    - 750 lm, working time: 5 h
    - 1500 lm, working time: 2 h 30 min
    - 2300 lm, working time: 1 h 30 min



Compact LED floodlight for professional use. Provides uniform and stable directional lighting. Made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC), transmits up to 80 % of the light emitted by the LEDs. The smaller size and compact design make it convenient to transport. It is equipped with a switch with 4-step luminous flux control. It can be mounted on a stand, significantly increasing the range and comfort of use.

**MAGNUM BATTERY XS** is also available as a set with a capacious and durable Bosch battery and charger. The battery is compatible with other Bosch devices in the 18V Professional System.



Item no.	Description
0509013	Luminaire Magnum Battery XS + 1x Bosch battery 2Ah
0509020	Luminaire Magnum Battery XS + 1x Bosch battery 2Ah + Bosch quick charger GAL 18V-40
0509303	Luminaire Magnum Battery XS + 2x Bosch batteries 2Ah
0509310	Luminaire Magnum Battery XS + 2x Bosch batteries 2Ah + Bosch quick charger GAL 18V-40

## Magnum Battery M Set



- Impact resistance: IK10
- Nominal power: 30 W
- Color temperature: 4000 K
- **Max. luminous flux: 4050 lm**
- Operating mode for battery-based operation for 2 Ah batteries:
  - 4 brightness levels:
    - 500 lm, working time: 9 h
    - 1850 lm, working time: 2 h 30 min
    - 2750 lm, working time: 1 h 30 min
    - 4050 lm, working time: 1 h



Compact LED floodlight for professional use. Provides uniform and stable directional lighting. Made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC), transmits up to 80 % of the light emitted by the LEDs. Magnum Battery M is the second-largest luminaire from the Magnum Battery Series, but is still easy to transport and is characterized by a higher impact resistance (IK10) and a higher maximum value of the luminous flux. It is equipped with a switch with 4-step luminous flux control. It can be mounted on a stand, significantly increasing the range and comfort of use.

**MAGNUM BATTERY M** is also available as a set with a capacious and durable Bosch battery and charger. The battery is compatible with other Bosch devices in the 18V Professional System.



Item no.	Description
0509327	Luminaire Magnum Battery M + 1x Bosch Battery 2Ah + Stand 2 m with CLICK Function
0509334	Luminaire Magnum Battery M + 1x Bosch Battery 2Ah + Quick Charger Bosch GAL 18V-40 + Stand 2 m with CLICK Function
0509341	Luminaire Magnum Battery M + 2x Bosch Battery 2Ah + Stand 2 m with CLICK Function
0509358	Luminaire Magnum Battery M + 1x Bosch Battery 2Ah + Quick Charger Bosch GAL 18V-40 + Stand 2 m with CLICK Function

# Luminaires for the professional user!

#loveled



## Magnum Battery L Set



- Impact resistance: IK10
- Nominal power: 70 W
- Color temperature: 4000 K
- **Max. luminous flux: 9250 lm**
- Operating mode for battery-based operation for 2 Ah batteries:
  - 4 brightness levels:
    - 1000 lm, working time: 5 h
    - 3800 lm, working time: 1 h 15 min
    - 5650 lm, working time: 45 min
    - 9250 lm, working time: 25 min

Compact LED floodlight for professional use. Provides uniform and stable directional lighting. Made of impact-resistant polypropylene (PP). Anti-glare diffuser made of polycarbonate (PC), transmits up to 80 % of the light emitted by the LEDs. The most powerful and largest floodlight from the Magnum Battery family. The maximum luminous flux value is 9250 lm. It is equipped with a switch with 4-step luminous flux control. It can be mounted on a stand, significantly increasing the range and comfort of use.

**MAGNUM BATTERY L** is also available as a set with a capacious and durable Bosch battery and charger. The battery is compatible with other Bosch devices in the 18V Professional System.



Item no.	Description
0509365	Luminaire Magnum Battery L + 1x Bosch Battery 2Ah + Stand 2 m with CLICK Function
0509372	Luminaire Magnum Battery L + 1x Bosch Battery 2Ah + Quick Charger Bosch GAL 18V-40 + Stand 2 m with CLICK Function
0509389	Luminaire Magnum Battery L + 2x Bosch Battery 2Ah + Stand 2 m with CLICK Function
0509396	Luminaire Magnum Battery L + 2x Bosch Battery 2Ah + Quick Charger Bosch GAL 18V-40 + Stand 2 m with CLICK Function

## Giant LED EVO



- Electrical protection class: IP54
- Power: 227 W
- **Max. luminous flux: 33144 lm**
- Protection class: I
- Light source: highly efficient SMD LED
- Impact-resistant casing and ergonomic handle
- Anti-glare diffuser made of polycarbonate
- Cables: H07RN-F 3x 1.5 mm<sup>2</sup> (5 m)
- Two sockets on the back that allow the connection of other electrical devices or serial luminaire connection
- Net weight: 5.3 kg

Item no.	Description
0501256	Giant LED EVO with two sockets

## Stand for Giant LED EVO



- Steel tripod
- Extended length: max. 3 meters
- Folded length: 1.22 meters
- Leg spacing: 134 cm
- Pipe diameter (leg): 2.5 cm
- Load capacity: 30 kg
- Net weight: 5.4 kg
- Color: black
- Accessories: Adapter plate with screw function for Giant Luminaires

Item no.	Description
0500294	Stand for Giant LED EVO 3 m
0500300	Adapter plate with screw function for mounting the Giant Luminaire on the tripod

## Magnum Battery XS



- Impact resistance: IK09
- Nominal power: 20 W
- Color temperature: 4000 K
- Supply voltage: 18V
- Protection class: III
- **Max. luminous flux: 2300 lm**
- Operating modes for battery-based operation for 2 Ah batteries:
  - 4 brightness levels:
    - 200 lm, working time: 15 h
    - 750 lm, working time: 5 h
    - 1500 lm, working time: 2 h 30 min
    - 2300 lm, working time: 1 h 30 min

Item no.	Description
0509006	Magnum Battery XS (without battery and charger)

## Magnum Battery M



- Impact resistance: IK10
- Nominal power: 30 W
- Color temperature: 4000 K
- Supply voltage: 18V
- Protection class: III
- **Max. luminous flux: 4050 lm**
- Operating modes for battery-based operation for 2 Ah batteries:
  - 4 brightness levels:
    - 500 lm, working time: 9 h
    - 1850 lm, working time: 2 h 30 min
    - 2750 lm, working time: 1 h 30 min
    - 4050 lm, working time: 1 h

Item no.	Description
0509228	Magnum Battery M (without battery and charger)



## Magnum Battery L



- Impact resistance: IK10
- Nominal power: 70 W
- Color temperature: 4000 K
- **Max. luminous flux: 9250 lm**
- Supply voltage: 18V
- Protection class: III
- Operating modes for battery-based operation for 2 Ah batteries:
- 4 brightness levels:
  - 1000 lm, working time: 5 h
  - 3800 lm, working time: 1 h 15 min
  - 5650 lm, working time: 45 min
  - 9250 lm, working time: 25 min

Item no.	Description
0509259	Magnum Battery L (without battery and charger)

## Magnum Future LED XS



- Impact resistance: IK10
- Electrical protection class: IP44
- Nominal power: 20 W
- Color temperature: 4000 K
- **Max. luminous flux: 2300 lm**
- Supply voltage: 220 – 240V
- Protection class: I
- Luminaire casing material: PP
- Diffuser material: PC
- Beam angle: 120°
- Cables: H07RN-F 3x 1.5 mm<sup>2</sup> (3 m)
- One socket on the back that allows the connection of other electrical devices or serial luminaire connection
- Net weight: 1 kg

Item no.	Description
0508405	Magnum Future LED XS with socket

## Flato LED L Set with Stand



- Impact resistance: IK07
- Electrical protection class: IP54
- Rated power of the luminaire: 47 W
- Color temperature: 4000 K
- **Max. luminous flux of a luminaire: 4600 lm**
- The set consists of 2 Flato L lamps and stand
- Luminaire casing material: PP
- Stand: Extended/folded length: 200 cm/108 cm
- Leg spacing: 92 cm
- Pipe diameter (leg): 3.5 cm
- Load capacity: 15 kg

Item no.	Description
0502359	Set 2x Flato LED L with Stand 2 m

## Flato LED L (single)



- Impact resistance: IK07
- Electrical protection class: IP54
- Nominal power: 47 W
- Color temperature: 4000 K
- **Max. luminous flux: 4600 lm**
- Protection class: I
- Light source: LED Module
- Luminaire casing material: PP
- Diffuser material: PC
- Diffuser type: OPAL
- Cables: H20RN-F 2x 1 mm<sup>2</sup> (3 m)

Item no.	Description
0502199	Flato LED L

## Magnum Future LED XL



- Impact resistance: IK10
- Electrical protection class: IP54
- Nominal power: 78 W
- Color temperature: 4000 K
- **Max. luminous flux: 11000 lm**
- Supply voltage 220 – 240V
- Protection class: I
- Diffuser type: frozen
- Two sockets on the back that allow the connection of other electrical devices or serial luminaire connection as well as an on/off switch
- Cables: H07RN-F 3x 1.5 mm<sup>2</sup> (5 m)

Item no.	Description
0508887	Magnum Future LED XL MAX with 2 sockets

## Magnum Future LED XS Akku



- Impact resistance: IK10
- Electrical protection class: IP54/20
- Nominal power: 20 W
- Color temperature: 4000 K
- **Max. luminous flux: 2000 lm**
- Supply voltage: 220 – 240 V
- Protection class: II
- Charging time: 4 h
- 3 brightness levels:
  - 650 lm, working time: 6 h
  - 1000 lm, working time: 4 h
  - 2000 lm, working time: 2 h
- Luminaire casing material: PP
- Including charger

Item no.	Description
0508511	Magnum Future LED XS Battery

## Plaster Lite Future LED



Stand  
(see p. 10)

- Impact resistance: IK07
- Electrical protection class: IP66
- Nominal power: 49 W
- Color temperature: 4000 K
- **Max. luminous flux: 6400 lm**
- Protection class: I
- Supply voltage: 220 – 240V
- Cables: H07RN-F 3x 1.5 mm<sup>2</sup> (5 m)
- **Without a stand**

Item no.	Description
0509217	Plaster Lite Future LED

## Future Ball LED



- **Sphere of light**
- Impact resistance: IK10
- Electrical protection class: IP54
- Nominal power: 20 W
- **Max. luminous flux: 2400 lm**
- Protection class: I
- Light source: highly efficient LED
- Housing: PP
- Even light distribution
- Foldable hook
- Cables: H07RN-F 3x 1.5 mm<sup>2</sup> (5 m)
- Integrated cable reel
- Two sockets that allow the connection of other electrical devices or serial luminaire connection

Item no.	Description
0509212	Future Ball LED with two sockets and an on/off switch



# Magnum Multi Battery!

New, innovative battery adapter system that allows luminaire usage to be controlled with the help of various battery systems. Exactly the right lamp for users of cordless tools with an 18V battery of the following manufacturers:

- Bosch Professional
- Milwaukee
- DeWalt
- Berner

Item no.	Description
0509068	Magnum Multi Battery XS 2300 lm + Adapter
0509075	Magnum Multi Battery M 4050 lm + Adapter
0509082	Magnum Multi Battery L 9250 lm + Adapter



## VARIANTS



Magnum Multi Battery **XS**  
2300 lm



Magnum Multi Battery **M**  
4050 lm



Magnum Multi Battery **L**  
9250 lm



Adapter

# Impact-resistant luminaire

## FOR PROFESSIONALS

HIGH LUMINOUS FLUX IN  
A ROBUST AND LIGHT-WEIGHT HOUSING



## Site Lite Future LED



- Electrical protection class: IP54/20
- Nominal power: 20 W
- Color temperature: 4000 K
- **Max. luminous flux: 2000 lm**
- Protection class: III
- Frequency: 50 – 60 Hz
- Beam angle: 360°
- Luminaire casing material: PP + T
- Diffuser material: PC
- Color rendering index (Ra): >80
- Charging time: 4 h
- Battery working time: 6 h
- 3 brightness levels
- Including charger

Item no.	Description
0501444	Site Lite Future LED

## Stand



- Tripod with Click Head System
- Compatible with: Magnum Family and Plaster Lite Future LED
- Extended length: 2 m
- Folded length: 108 cm
- Leg spacing: 92 cm
- Pipe diameter (leg): 3.5 cm
- Load capacity: 15 kg
- Net weight: 2.3 kg
- Color: black

Item no.	Description
0500737	Stand

## Crop Future LED



- Light source: 4 W COB LED + 4 W SMD LED (top)
- Lighting time: 400 lm – 3.5 h, 120 lm – 10 h
- Electrical protection class: IP54
- Protection class III
- USB charger included in set
- Net weight: 110 g
- Battery Li-ion 3.7V 2600 mAh
- Charging time: 3 h
- Strong magnet in base
- Movable handle +/- 180°

Item no.	Description
0508599	Crop Future LED

## Cyclop LED



- **Gesture control**
- Light source: COB LED
- Lighting time: 300 lm – 2.5 h, 150 lm – 4 h
- Protection class III
- USB charger included in set
- Net weight: 110 g
- Battery Li-ion 3.7 V 1500 mAh
- Charging time: 3 h
- Indicator of battery charging state
- Non-slip strap
- Modern design and materials of the highest quality
- Movable luminaire head +/- 60°

Item no.	Description
0504689	Cyclop LED

## Avior COB LED



- Light source: 2 W COB LED + 1 W SMD LED (top)
- Luminous flux: 2 W COB – 200 lm, 1 W SMD – 100 lm
- Strong magnet in base
- Protection class III
- Retractable rotatable hook in the housing
- USB charger included in set
- Battery Li-ion 3.7V 2200 mAh
- Luminaire covered with rubber
- Charging time: 3 h
- Lighting time: 3.5 h – Main luminaire, 8 h – flashlight
- Indicator of battery charging state
- Movable handle +/- 180°

Item no.	Description
0504719	Avior COB LED

## Crane COB LED



- Light source: 5 W COB LED + 1 W SMD LED (top)
- Luminous flux: 5 W COB – 450 lm, 1 W SMD – 120 lm
- Strong magnet in base
- Protection class III
- USB charger included in set
- Battery Li-ion 3.7V 2600 mAh
- Luminaire covered with rubber
- Charging time: 3 h
- Lighting time: 3 h – High, 5.5 h – Low
- Battery level and low battery indicator
- Luminaire movable in the range of 120°
- Movable luminaire neck +/- 120°

Item no.	Description
0504764	Crane COB LED

## Profi Slim Service Set



- Light source: SMD LED
- Power: 12 W
- **Max. luminous flux: 1200 lm**
- Electrical protection class: IP44
- Matt diffuser made of polycarbonate
- Handle and cap made of ABS
- Rubber cable: H05RR-F 2 x 1 mm<sup>2</sup> (5 m)
- Possibility to buy and replace assemblies
- Bracket made of aluminum
- Bracket spacing: 105 – 170 cm
- Net weight with luminaire: 1.2 kg
- Ideal for vehicle workshops for illuminating the engine compartment and for use in car preparation

Item no.	Description
0508232	Profi Slim Service Set

## Profi Slim Line LED



- Light source: SMD LED
- Power: 2x 14 W
- **Max. luminous flux: 2550 lm**
- Electrical protection class: IP65
- Impact-resistant casing
- Anti-glare diffuser made of frozen polycarbonate
- Luminaire length: 120 cm each
- Cables: H07RN-F 3x 1.5 mm<sup>2</sup> (5 m)
- Ideal for illuminating lifting platforms

Item no.	Description
0508805	2x Profi Slim Line LED including power supply unit, wiring and mounting bracket
0508751	Magnetic bracket (1 pc.)
0508768	Screw bracket (2 pcs.)

## Type 101 LED



- Light source: LED
- Electrical protection class: IP54
- Rated power of the luminaire: 12 W
- Impact resistance: IK10
- Color temperature: 4000 K
- **Max. luminous flux: 1700 lm**
- Protection class: II
- Color rendering index (Ra): >80, SDCM: ≤ 3
- Length: 70 cm
- Cables: H05RN-F 3x 0.75 mm<sup>2</sup> (5 m)
- Ideal for illuminating workplaces and lifting platforms

Item no.	Description
0508809	Type 101 LED
0509140	Mounting bracket

## Clima Evo UV



- Power: 1 W
- Light source: UV LED
- Aluminum casing
- High protection class: IP54
- Switch in the housing
- Net weight: 0.2 kg
- Included in set:
  - Black strap
  - Batteries (6 x AAA)
  - UV glasses
- Luminaire for diagnosing air conditioning leaks

Item no.	Description
0508575	Clima EVO UV

## Eye COB LED



- Light source: COB LED
- Lighting time: 500 lm – 2.5 h, 250 lm – 5 h, 100 lm – 10 h
- Upper rotatable part in the range of 1800 horizontally and 1200 vertically
- Strong magnet in base
- Protection class III
- Rotatable hook
- USB charger included in set
- Net weight: 0.33 kg
- Battery Li-ion 3.7V 2600 mAh
- Luminaire covered with rubber
- Charging time: 4 h
- Indicator of battery charging state
- Point lighting

Item no.	Description
0504641	Eye COB LED

## Cobus COB LED



- Light source: COB LED
- Luminous flux: 290 lm
- Upper rotatable part in the range of 180° horizontally and 120° vertically
- Strong magnet in base
- Protection class III
- Rotatable hook
- USB charger included in set
- Net weight: 0.3 kg
- Very light design
- Battery Li-ion 3.7V 2200 mAh
- Luminaire covered with rubber
- Charging time: 4 h
- Lighting time: 4 h
- Indicator of battery charging state

Item no.	Description
0504559	Cobus COB LED

## Diuna COB LED



- Light source: COB LED
- Luminous flux: 200 lm
- Strong magnet in base
- Protection class III
- Rotatable hook
- Net weight: 0.2 kg
- Battery Li-ion 3.7V 2200mAh
- Luminaire covered with rubber
- Lighting time: 5 h
- Charging time: 4 h
- Indicator of battery charging state
- Charge via integrated USB

Item no.	Description
0504665	Diuna COB LED

## Drago LED



- Light source: COB LED
- Luminous flux: 2 W COB – 220 lm – High, 100 lm – Low
- Strong magnet in base
- Flashlight function
- Protection class III
- Retractable rotatable hook in the housing
- USB charger included in set
- Net weight: 0.175 kg
- Battery Li-ion 3.7V 1500 mAh
- Charging time: 4 h
- Lighting time: 4 h
- Movable handle +/- 180°

Item no.	Description
0504566	Drago LED

## Optim LED



- Light source: SMD LED
- Power: 2 W
- Electrical protection class: IP20
- **Max. luminous flux: 230 lm**
- Protection class: II
- Cover made of PVC
- Cap and handle made of PP
- Swivel suspension
- Net weight: 0.4 kg
- Cables: H05W-F 2 x 0.75 mm<sup>2</sup> (5 m)

Item no.	Description
0505958	Optim LED

## Magnum Hobby



- Impact resistance: IK10
- Electrical protection class: IP44
- Rated power of the luminaire: 32 W
- Color temperature: 4000 K
- **Luminous flux: 3600 lm**
- Supply voltage: 220 – 240V
- Protection class: II
- Luminaire casing material: PP
- Luminaire casing color: green
- Diffuser material: PC
- Cables: H07RN-F 2x 1 mm<sup>2</sup> (3 m)

Item no.	Description
0506447	Magnum Hobby





## Handy Future LED



- Light source: 3 W COB LED + 3 W LED
- Luminous flux: 60 and 150 lm
- Strong magnet in base
- Durable casing
- 2 lighting modes
- Electrical protection class: IP20
- Rotatable hook
- Charging time: 3.5 h
- Lighting time: 2.5 h
- Indicator of battery charging state
- Including charger

Item no.	Description
0508551	Handy Future LED

## Handy Multi LED



- Light source: 5 W COB LED + 2 x 3 W LED
- Luminous flux: 240 and 400 lm
- Strong magnet in base
- Durable casing
- 2 lighting modes
- Electrical protection class: IP40
- Charging time: 3.5 h
- Lighting time: 2,5 – 4 h
- Stepless dimming and brightening
- Including charger

Item no.	Description
0508568	Handy Multi LED

## Classic Outdoor



- Light source: LED E27 Luminaire
- Galvanized steel protective grille
- Glass diffuser
- Bracket and protection ring made of rubber
- Protection class: II
- Cables: H05VV-F 2x 0.75 mm<sup>2</sup> (5 m)
- Net weight: 0.85 kg
- Increased ingress protection of the luminaire in class IP44
- **Without bulbs**

Item no.	Description
0500133	Classic Outdoor

## Classic Indoor



- Light source: E27
- Maximum source power: 60 W
- Galvanized steel protective grille
- Protection class: II
- Diffuser: PC
- Bracket made of plastic
- Net weight: 0.85 kg
- Cables: H05VV-F 2x 0.75 mm<sup>2</sup> (5 m)
- **Without bulbs**

Item no.	Description
0500058	Classic Indoor

# #loveled

WWW.SERWO.EU





Retailer:



**Serwo GmbH**  
Benzstraße 4 – 6  
D-51381 Leverkusen

order@serwo.eu  
www.serwo.eu

**Your contact**  
Mr. Jens Schulze  
jens.schulze@serwo.eu

